



**SHERWIN
WILLIAMS.**

103.20

PROMAR[®] 200

INTERIOR ALKYD EG-SHEL

B33 SERIES

As of 10/15/2010, Complies with:			
OTC	No	LEED [®] 09 CI	No
SCAQMD	No	LEED [®] 09 NC	No
CARB	No	LEED [®] 09 CS	No
MPI Spec #	51	LEED [®] 09 H	No
NGBS	No		

CHARACTERISTICS

ProMar[®] 200 Interior Alkyd Eg-Shel is our professional best quality product. This product is recommended for interior application on primed plaster, wall-board, wood, masonry, and primed metal.

Color: Most colors

To optimize hide and color development, always use the recommended P-Shade primer

Coverage: 350 - 400 sq ft/gal
@ 4 mils wet; 1.8 mils dry

Drying Time, @ 77°F, 50% RH:

Touch: 2-4 hours
Recoat: 24 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Finish:

24 hours 25-35 units @ 60°
30 days 20-30 units @ 60°

Flash Point: 109°F, PMCC

Tinting with Blend-A-Color:

Base	oz/gal	Strength
Luminous White	0-5	125%
Extra White	0-5	100%
Deep Base	4-12	100%

Vehicle Type: Alkyd

B33W00251

VOC (less exempt solvents):

435 g/L; 3.63 lb/gal

Volume Solids: 44 ± 2%

Weight Solids: 65 ± 2%

Weight per Gallon: 10.3 lb

Not OTC Compliant

SPECIFICATIONS

Block

1 ct. Loxon Block Surfacer
2 cts. ProMar 200 Interior Alkyd Eg-Shel

Drywall

1 ct. ProMar 200 Latex Primer
2 cts. ProMar 200 Interior Alkyd Eg-Shel

Plaster

1 ct. Premium Wall and Wood Primer
2 cts. ProMar 200 Interior Alkyd Eg-Shel

Masonry

1 ct. Loxon Masonry Primer
2 cts. ProMar 200 Interior Alkyd Eg-Shel

Wood

1 ct. Premium Wall and Wood Primer
2 cts. ProMar 200 Interior Alkyd Eg-Shel

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Seal glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with an appropriate primer/sealer.

Drywall

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Masonry Primer.

103.20

PROMAR[®] 200

INTERIOR ALKYD EG-SHEL

B33 SERIES



**SHERWIN
WILLIAMS.**

SURFACE PREPARATION

Plaster

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Wood

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

Caulking

Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

APPLICATION

Apply at temperatures above 50°F.

No reduction necessary

Brush

Use a natural bristle brush.

Roller

Use a 1/4" - 3/4" nap synthetic or lamb-swool roller cover.

Spray—Airless

Pressure 2000 psi

Tip015"-.021"

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

Non-photochemically reactive.

For exterior use on doors, trim, and other small areas of wood or metal. Do not use on the main body of exterior structures.

DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

LABEL CAUTIONS

CAUTION contains ALIPHATIC HYDROCARBONS. Contents are **COMBUSTIBLE**. Keep away from heat and open flame. **VAPOR HARMFUL**. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**
HOTW 10/15/2010 B33W00251 10 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.