



108.42A

QUICK DRY

Interior/Exterior Latex Stain Blocking Primer

B51W08670

As of 08/01/2013, Complies with:			
OTC	Yes	LEED® 09CI	Yes
SCAQMD	Yes	LEED® 09NC	Yes
CARB	Yes	LEED® 09CS	Yes
CARB SCM 2007	Yes	LEED® H	Yes
MPI #	No	NGBS	Yes

PRIMARY BENEFITS

- **Good Value** — This is a multi-purpose commercial primer formulated for general interior and exterior use.
- **Quick Drying** — As the name suggests, this primer dries in just one hour, so rooms can be topcoated soon after priming.
- The waterborne formula is user-friendly, delivering easy clean-up with soap and water.
- **Good Stain-Blocking Properties** — Effectively blocks stains from crayon, permanent marker, pencil, mustard, ketchup, and tea
- **Versatile** — Use Quick Dry Stain Blocking Primer to prime and seal new and previously painted drywall, wood, masonry and plaster.
- **Color Selection** — Quick Dry Stain Blocking Primer can be tinted or used as a packaged color.

Use on:

- Wood
- Plywood
- Masonry (pH 6-9)
- Stucco (pH 6-9)
- Cement Composition (pH 6-9)
- Aluminum
- Galvanized Steel
- Previously painted surfaces

CHARACTERISTICS

Color: White
Coverage: 350 - 400 sq ft/gal @ 4 mils wet; 1.1 mils dry
Drying Time, @ 77°F, 50% RH:
 Touch: 30 minutes
 Recoat as a primer 1 hour
 Recoat as a stain sealer: 4 hours
 Drying and recoat times are temperature, humidity and film thickness dependent.
Finish: 0-5 units @ 85°
Flash Point: N/A
Vehicle Type: Vinyl Acrylic

B51W08670

VOC (less exempt solvents):
 <50 g/L; <0.42 lb/gal
 As per 40 CFR 59.406 and SOR/2009-264, s.12
Volume Solids: 29 ± 2%
Weight Solids: 43 ± 2%
Weight per Gallon: 10.4 lb

Tinting

Requires ColorCast Ecotoners for tinting. For best topcoat color development, use the recommended "P"-shade primer. If desired, up to 4 oz per gallon of Color-Cast Ecotoners can be used to approximate the topcoat color. Check color before use.

When spot priming on some surfaces, a non-uniform appearance of the final coat may result, due to differences in holdout between primed and unprimed areas. To avoid this, prime the entire surface rather than spot priming.

For optimal performance, this primer must be topcoated with a latex, alkyd/oil, water based epoxy, or solvent based epoxy coating on architectural applications.

For exterior exposure, this primer must be topcoated within 14 days with architectural latex or oil finishes.

For better performance when priming an entire house, use Exterior Latex or Oil-Based Primers.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.

Drywall - Fill cracks and nail holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry & Concrete

All new surfaces must be cured according to the supplier's recommendations, usually about 30 days. Remove all form release and curing agents. Masonry surfaces must be dry before priming. Moisture content must be 15% or lower and the pH between 6 and 9.

Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.



108.42A

QUICK DRY

Interior/Exterior Latex Stain Blocking Primer B51W08670

<u>SURFACE PREPARATION</u>	<u>APPLICATION</u>	<u>CAUTIONS</u>
<p>Plaster Must be cured, usually 30 days, and hard. If painting cannot wait, allow the surface to dry 7 days and prime with Loxon Concrete and Masonry Primer. Soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry before painting.</p> <p>Wood & Plywood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p>Caulking Fill gaps between walls, ceilings, crown moldings, and other trim with the appropriate caulk after priming the surface.</p> <p>Special recommendations After priming stained areas, allow to dry 4 hours, test a small area for bleeding by applying the topcoat before painting the entire project. If the stain bleeds through, apply a second coat of primer and allow to dry overnight and retest before topcoating. Some water sensitive stains may require the use of an oil-based primer to seal completely.</p>	<p>Apply at temperatures above 50°F. No reduction necessary. Do not thin when used for stain blocking.</p> <p>Brush Use a nylon/polyester brush</p> <p>Roller Use a 1/4" - 3/4" nap synthetic cover</p> <p>Airless Spray Pressure..... 2000 psi Tip..... .017"-.021"</p> <p><u>CLEANUP INFORMATION</u></p> <p>Clean spills, spatters, hands and tools with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.</p>	<p>Protect from freezing. Non-photochemically reactive. Not for use under wallpaper. Not for use on vinyl or other plastic surfaces.</p> <p>LABEL CAUTIONS CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p> <p>HOTW 10/29/2012 B51W08670 06 00</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>